

## 2012 V8 Xtreme

### ELIGIBLE MODELS - Open to all V8 steel body cars

#### Battery

- 1 It is recommended that the battery remain under hood in stock location and be well secured. If the battery is removed from stock location, it shall be secured in a sealed battery box and meet tech approval

#### Tires

- 1 Tire permitted will have a tread with no greater than 8"

#### Gas Tank:

- 1 If stock gas tank is behind rear axle, it must be replaced or contained in the trunk area as far forward as possible. No further forward than the spreader bar. **IT IS HIGHLY RECOMMENDED THAT THIS FUEL CONTAINER BE REPLACED WITH A COMMERCIALY PRODUCED FUEL CELL.** All fuel container applications must be tech approved.

#### Car Construction

- 1 Exterior bracing, bumper reinforcement and nerf bars approved.
- 2 Front bumper area may be reinforced.
- 3 Four point roll cage highly recommend. Minimal allowance will be the following – H Post consists of 2 upright bars required using 1 3/4" (.095") minimum pipe with steel plates on each end for mounting. Mounted vertically from floorboard to roof with no less than 7/16" bolts and washers. Upright bars are required to have at least one 1 3/4" o.d. (.095) minimum kicker bar from the top of the upright posts down to the floor at an angle, and welded to the upright bars and bolted or welded to the floor at the frame. The upright bars must be connected at the top and welded together by a connecting bar. Any cars without roll cage, must have 12" C channel door bar on the driver's side and 8" door bar on the passenger side. **Any variation of roll over protection shall be approved by an Evergreen Speedway tech official.**

- 4 Windshield may remain if in good condition or may be replaced by lexan or maximum 1" by 1" screen. All other glass, and under hood insulation must be removed. ½" lexan will be permitted.
- 5 All doors must be welded, bolted or chained shut. A driver's door plate is required of no less than 3" wide x ¼" thick steel flat strap extending past the front and rear door seams in the middle of the door skin. The purpose of the strap is to not only keep the door closed but to provide some impact resistance. It is recommended that more than one of these straps be installed. All straps must be installed flat. Grader blade material is highly recommended as strap material.

### **Car Numbers**

- 1 Must be at least 12 inches tall and in contrasting color on the driver and front passenger doors and a car number on the roof. No duplicate numbers allowed.

### **Personal Protection**

- 1 Approved helmet, Snell 2000 minimum requirement.
- 2 5 point racing seat belts are MANDATORY. (3 yr date stamp recommended) **All belts must be approved by an Evergreen Speedway tech official.**
- 3 Long sleeve fire retardant jacket required, full length Nomex racing suit highly recommended. Long pants and full leather shoe or boot and gloves required. No nylon allowed PERIOD. Racing suit, gloves and neck brace highly recommended.

### **Management Claim**

- 1 There is no claimer in effect.

All cars are subject to a minimum specification inspection at any time. It is the responsibility of the driver to prepare their car free of defects and in safe racing condition.